



Technical Informations / Teknik Bilgiler

Thread size / Anma çapı (d)		M3	M4	M5	M6	M8	M10	M12	M14
Pitch / Diş adımı	P	0,50	0,70	0,80	1,00	1,25	1,50	1,75	2,00
Head height / Kafa yüksekliği	max.	3,00	4,00	5,00	6,00	8,00	10,00	12,00	14,00
	k min.	2,86	3,82	4,82	5,70	7,64	9,64	11,57	13,57
Head dia / Kafa çapı	d max.	5,50	7,00	8,50	10,00	13,00	16,00	18,00	21,00
	d min.	5,32	6,78	8,28	9,78	12,73	15,73	17,73	20,67
Socket width / Soket genişliği	s min.	2,50	3,00	4,00	5,00	6,00	8,00	10,00	12,00
	s max.	2,52	3,02	4,02	5,02	6,02	8,03	10,03	12,03
Socket dia / Soket çapı	e min.	2,87	3,44	4,58	5,72	6,86	9,15	11,43	13,72
	e max.	2,58	3,08	4,10	5,14	6,14	8,18	10,18	12,21
Socket depth / Soket derinliği	t	1,30	2,00	2,50	3,00	4,00	5,00	6,00	7,00
Thread length / Diş uzunluğu	b ¹	18,00	20,00	22,00	24,00	28,00	32,00	36,00	40,00
	b ²	Fully threaded. /Tam dişli.							

Thread size / Anma çapı (d)		M3	M4	M5	M6	M8	M10	M12	M14
Length / Boy	min.								
	max.								
		Weight/Ağırlık gr/p							
5	4,76	5,24	0,67						
6	5,76	6,24	0,71	1,50					
8	7,71	8,29	0,80	1,65	2,45				
10	9,71	10,29	0,88	1,80	2,70	4,70			
12	11,65	12,35	0,96	1,95	2,95	5,07	10,90		
16	15,65	16,35	1,16	2,25	3,45	5,75	12,10	20,90	
20	19,58	20,42	1,36	2,65	4,01	6,53	13,40	22,90	32,10
25	24,58	25,42	1,61	3,15	4,78	7,59	15,00	25,40	35,70
30	29,58	30,42	1,86	3,65	5,55	8,30	16,90	27,90	39,30
35	34,50	35,50		4,15	6,32	9,91	18,90	30,40	42,90
40	39,50	40,50		4,65	7,09	11,00	20,90	32,90	46,50
45	44,50	45,50			7,86	12,10	22,90	36,10	50,10
50	49,50	50,50			8,63	13,20	24,90	39,30	54,50
55	54,40	55,60				14,30	26,90	42,50	58,90
60	59,40	60,60				15,40	28,90	45,70	63,40
65	64,40	65,60					31,00	48,90	67,80
70	69,40	70,60					33,00	52,10	71,30
80	79,40	80,60					37,00	58,50	80,20

Values are given in millimeters. / Değerler milimetre olarak verilmiştir.